

IN THE CLAIMS:

Amend claims 1, 4 and 5 as shown below.

Add new claims 6 and 7 as shown below.

1. (currently amended) An apparatus for eliminating dross from liquid solder in a solder pot of a soldering machine comprised of: a means for breaking up the said dross into small particles and recirculating said liquid solder, said dross and a ~~non-dross non-~~ solder residue in said solder pot; a shroud having a lower opening in adjacent and covering relationship to a free surface of said liquid solder in said solder pot; a chemical de-oxidizing agent ~~for separating~~ to separate said dross into liquid solder and said non-solder residue; and a vacuum source connected to said shroud for removing a portion of said non-solder residue when a said portion of said non-solder residue is adjacent to said lower opening of said shroud.

2. (original) The apparatus recited in claim 1 further comprising a means in said solder pot for directing a flow of said liquid solder and said non-solder residue in said solder pot.

3. (original) The apparatus recited in claim 1 wherein said de-oxidizing agent is a mixture of a potassium salt and borohydrochloride.

4. (currently amended) The apparatus recited in claim 1 wherein said means for

breaking up and recirculating said liquid solder, said dross and said non-solder residue is an impeller.

5. (currently amended) A method for eliminating dross from solder in a solder pot of a soldering machine comprised of the steps of: breaking up said dross into small particles and recirculating said solder, said dross and a non-solder residue in said solder pot; adding a chemical de-oxidizing agent to a said solder pot ~~containing liquid solder~~ to chemically divide said dross into liquid solder and a said non-solder residue; ~~breaking up and recirculating said liquid solder and said non-solder residue in said solder pot~~; and applying a vacuum to said non-solder residue to remove said non-solder residue from said solder pot.

7. (new) A method for eliminating dross from liquid solder in a solder pot of a soldering machine comprising the steps of: adjusting a height of a dross reservoir in a solder pot to allow solder in said solder pot to flow into said reservoir; directing a flow of said solder with a solder guide toward a top of the solder pot to form a main solder wave; directing a flow of a portion of said solder into said dross reservoir; and mixing said solder in said dross reservoir with an anti-oxidant agent to separate dross in said solder from said solder.

6. (new) An apparatus for eliminating dross from liquid solder in a solder pot of a soldering machine comprised of: an impeller for breaking up said dross into small particles

and recirculating said liquid solder, said dross and said non-solder residue in said solder pot; a shroud having a lower opening in adjacent and covering relationship to a free surface of said liquid solder in said solder pot; a mixture of a potassium salt and borohydrochloride to separate said dross into liquid solder and said non-solder residue; and a vacuum source connected to said shroud for removing a portion of said non-solder residue when said portion of said non-solder residue is adjacent to said lower opening of said shroud.